

PRIMER PO

(P.T.B.-PRIMER)

Ready-to-use primer



APPLICATIONS

Ready-to-use, colourless primer for walls, floors, and ceilings. PRIMER PO lowers porosity and reinforces the substrate. Suitable surfaces are: plaster work on cement base, plaster work on gypsum base, gypsum plaster board, gypsum plaster blocks, concrete, ... PRIMER PO is suitable for indoor as well as outdoor use.



DIRECTIONS FOR USE

PRIMER PO should always be applied to a porous, clean, healthy, dust and oilfree substrate. Shake well before use. PRIMER PO should be generously and undilutedly applied with a brush or a roller. Strongly absorbing undergrounds (such as aerated concrete, plasterwork on gypsum base, and etc.) should be treated twice. Drying time: about 2 to 3 hours.



SPECIAL APPLICATIONS

PRIMER PO can be used as basic layer - on the adhesive side - to protect certain types of natural stone (for instance, white marble) against spot blemishes and staining. To be applied in 1 or 2 layers. It is recommended that a test be carried out first.



REMARKS

- The application tools should be cleaned with water directly after use.
- Do not use at temperatures below +5 °C or on top of a substrate where the temperature is below +5 °C.
- Store in a dry and frost-free place.



+30 °

+5 °

| Mixing ratio | Consumption | Packaging |
|--------------------------------------|---|-------------------------|
| Undiluted | ±0,050 to 0,150 l/m ² , depending on the porosity of the substrate | 1 L and 5 L |
| Colours | Drying time | Application temperature |
| Becomes colourless after application | ±2 to 3 hours | +5 °C till +30 °C |

As the applications of our products are diverse, no single application guideline can be laid down. All product data reflect the state of knowledge of our products at the time of publication. Therefore all suggestions and recommendations concerning the use of our products are merely illustrative. Apply the product on a small and insignificant spot before starting to use our products to be sure the desired result is obtained. Always ask for the technical sheet of our products. Visit the website www.compaktuna.be. Consult our "technical department" which can be reached for free on the green number 0800/92279. The Dutch text shall be exclusively binding. Version 10/02/2014. COMPAKTUNA BV is EN ISO 9001 certified.

COMPAKTUNA®
— Quality & Innovation —

 A MEMBER OF
HOLCIM GROUP

COMPAKTUNA bv/srl

Industriepark III
Industriepark Zwijnaarde 6
9052 Gent - Belgium
T +32 9 221 11 16
VAT BE0400.166.768 - R.P.R. Gent
info@compaktuna.be
www.compaktuna.be