

# DECLARATION OF PERFORMANCE

## Nr. 021/CPR/130701

1. Unique identification code of the product-type: **P.T.B.-DIKBED-FLEX**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
**P.T.B.-DIKBED-FLEX – Cementitious tile adhesive C2 TE**  
**(The batch number is printed on the packaging)**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:  
**Flexible tile adhesive for floor and wall, for internal and external use**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
**POLYTECHNISCH BEDRIJF BVBA/SPRL – P.T.B.-COMPAKTUNA®**  
**INDUSTRIEPARK ZWIJNAARDE 6**  
**9052 GENT - BELGIUM**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **Not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 12004+A1: 2012**  
  
The **BELGIAN BUILDING RESEARCH INSTITUTE (BBRI) No. 1136** carried out the determination of the product-type, the C2-performance, on the basis of type testing on samples taken by the manufacturer under system 3
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not relevant**
9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
<b>Reaction to fire</b>	<b>NPD</b>	<b>EN 12004+A1:2012</b>
<b>Bond strength as:</b>		
<b>-Initial tensile adhesion strength</b>	<b>≥ 1 N/mm<sup>2</sup></b>	
<b>Durability for:</b>		
<b>-Tensile adhesion strength after heat ageing</b>	<b>≥ 1 N/mm<sup>2</sup></b>	
<b>-Tensile adhesion strength after water immersion</b>	<b>≥ 1 N/mm<sup>2</sup></b>	
<b>-Tensile adhesion strength after freeze-thaw cycles</b>	<b>≥ 1 N/mm<sup>2</sup></b>	
<b>Release of dangerous substances</b>	<b>See MSDS</b>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


**DECLARATION OF PERFORMANCE**  
**Nr. 021/CPR/130701**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**K. SMESSAERT, Managing Director**  
(name and function)

**GENT, 01/07/2013**  
(place and date of issue)



(signature)