

DECLARATION OF PERFORMANCE
Nr. 083/CPR/130701

1. Unique identification code of the product-type: **FLEXcement® RAPID**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
FLEXcement® RAPID – Cementitious tile adhesive C2 FTE S1
(The batch number is printed on the packaging)
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Flexible tile adhesive for floor and wall, for internal and external use, rapid set tile adhesive
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
POLYTECHNISCH BEDRIJF BVBA/SPRL – P.T.B.-COMPAKTUNA®
INDUSTRIEPARK ZWIJNAARDE 6
9052 GENT - BELGIUM
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **Not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 12004+A1: 2012**

The **BELGIAN BUILDING RESEARCH INSTITUTE (BBRI) No. 1136** carried out the determination of the product-type, the C2-performance, on the basis of type testing on samples taken by the manufacturer under system 3

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not relevant**

9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	NPD	EN 12004+A1:2012
Bond strength as: -Tensile adhesion strength after 6 hours -Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ $> 1 \text{ N/mm}^2$	
Durability for: -Tensile adhesion strength after heat ageing -Tensile adhesion strength after water immersion -Tensile adhesion strength after freeze-thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
Release of dangerous substances	See MSDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


DECLARATION OF PERFORMANCE
Nr. 083/CPR/130701

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

K. SMESSAERT, Managing Director
(name and function)

GENT, 01/07/2013
(place and date of issue)

A handwritten signature in blue ink, consisting of several overlapping loops and a long horizontal stroke extending to the right.

(signature)