## P.T.B.-FLOORCOATING THINNER

## Thinner and cleaning agent for P.T.B.-FLOORCOATING



+35°

Application			
Properties	Thinner and cleaning agent for painting tools on a solvent basis, especially appropriate for use with P.T.BFLOORCOATING.		
Processing	Slowly evaporating thinner on the basis of aromatic hydrocarbons.		
	To be used undiluted for cleaning paint rollers and other painting tools. Also when using P.T.BFLOORCOATING.		
<b>Observations</b>			
	When the thinner is applied and drying, adequate aeration and ventilation shall be provided. P.T.BFLOORCOATING THINNER contains aromatic hydrocarbons.		
Packaging			
	500 ml cans, sold as 1 package together with 1 can of P.T.BFLOORCOATING, 1 can of P.T.BPRIMER PU and 2 solvent-resistant paint rollers. It can be kept for 2 years in the original, unopened packaging in a dry room at a temperature of between -20°C and + 40°C.		





Mixing ratio	-	Packaging
Undiluted	-	500 ml - sold as 1 package with 1 can of P.T.BFLOOR-COATING, 1 can of P.T.BPRIMER PU and 2 paint rollers
Colours		Application temperature
Colourless	-	+ 5°C up to + 35°C

As the applications of our products are diverse, no single application guideline can be laid down. All product data reflect the state of knowledge of our products at the time of publication. Therefore all suggestions and recommendations concerning the use of our products are merely illustrative. Apply the product on a small and insignificant spot before starting to use our products to be sure the desired result is obtained. Always ask for the technical sheet of our products. Visit the website www.compaktuna.be. Consult our "technical department" which can be reached for free on the green number 0800/92279. The Dutch text shall be exclusively binding.





Tradition & Quality