





P.T.B.-PASTAFIX

CE 1136	
POLYTECHNISCH BEDRIJF BVBA/SPRL – P.T.B.-COMPACTUNA® INDUSTRIEPARK ZWIJNAARDE 6 9052 GENT – BELGIUM	
13	
103/CPR/130701 EN 12004+A1 P.T.B.-PASTAFIX	
Dispersie tegelijm/wand en muur/binnen en buiten Colle dispersion/murs et sols/intérieur et extérieur Dispersion adhesive/floors and walls/internal and external Dispersionsklebstoff/Boden und Wand/Innen und Außen	
Brandklasse/Réaction au feu/Brandverhalten/Reaction to fire:	NPD
Hechtsterkte als/Force d'adhérence/Kiebkraft/Bond strength as:	
- initiele afschuifspanning/adherence initiale par cisaillement/Haltscherfestigkeit nach Trockenlagerung/initial shear adhesion strength	≥ 1 N/mm ²
Duurzaamheid/Stabilité d'adhérence/Haltbarkeit/Durability for: afschuifspanning/adherence en cisaillement/Haltscherfestigkeit/shear adhesion strength	
- na veroudering onder hoge warmte/après action de la chaleur/nach Wärmelagerung/after heat ageing	≥ 1 N/mm ²
- bij verhoogde temperatuur/à température élevée/bei erhöhter Temperatur/at elevated temperature	≥ 1 N/mm ²
- na onderdompeling in water/après immersion dans l'eau/ nach Wasserlagerung/after water immersion	≥ 0,5 N/mm ²
Vrijstelling gevaarlijke substanties/Emission de substances dangereuses/Freisetzung von gefährlichen Stoffen/Release of dangerous substances	MSDS

Super elastic tile glue (solvent free)



Characteristics



P.T.B.-PASTAFIX is a ready-for-use super elastic tile glue allowing to glue faience, ceramics, glass mosaics, etc. in a simple manner to a flat and clean surface.

Appropriate surfaces are: concrete, masonry, plaster, cementation works, cellular concrete, chipboards, veneer boards, etc.

Because of its researched composition, using P.T.B.-PASTAFIX results in a better adhesion than in the case of ordinary mortar. Applications in very fine layers are possible. With P.T.B.-PASTAFIX one never has leftovers nor waste, and moistening of the tiles and the surface is no longer required. P.T.B.-PASTAFIX is a waterproof tile glue that can be used both inside and outside.

P.T.B.-PASTAFIX can be used for applications in "wet rooms" such as e.g. showers, bathrooms, kitchens, etc.

P.T.B.-PASTAFIX cannot be used in a permanently wet environment (e.g. swimming pools). In such applications, we can recommend our products P.T.B.-KLEEFCEMENT and FLEXcement®.

After curing, P.T.B.-PASTAFIX does not present any deterioration and is insensitive to frost.

Mixing ratio	Consumption	Packaging
Undiluted	± 0,8 to 1,5 kg/m ²	1 kg (18 pcs/cardboard box), 7 kg and 14 kg
Colours	Open time	Application temperature
Broken white	± 15 min	+ 10°C till + 30°C

P.T.B.-PASTAFIX

Directions for use

P.T.B.-PASTAFIX is always applied on a clean, dust and oilfree surface. Boards serving as a surface must always be fixed in a stable way before the installation of the tiles is started. The adhesive is applied in a thin layer using an adhesive trowel or trowel, and then without delaying, the product is distributed evenly with an adhesive trowel. Next, the dry tiles are pressed on to the surface with a slightly twisting action. The tiles must be installed within fifteen minutes after application of the glue. Stopping of the joints of the tiles with pointing mortar is done after the glue has dried. Refer to our products P.T.B.-JOINT HY, P.T.B.-JOINT BREED and P.T.B.-EPOXY JOINT.

Remarks

- After use, the tools are cleaned with water without delaying so that the adhesive cannot remain stuck to the tools.
- In case the tiles shift down a little because of their weight, the appropriate spacers will be used.
- Conservation, processing and drying of the glue must be done away from frost.

