



P.T.B.-CLEANER

Cement veil remover



Characteristics



P.T.B.-CLEANER is a very powerful cement veil remover and cleansing agent. It removes chalk and cement veil from nearly all surfaces such as tiles, facing bricks, garage driveways and terraces. P.T.B.-CLEANER can also be used for descaling of tile walls, bath tubs, taps, etc...

1. Powerful acid cleaner with excellent cleansing properties for many surfaces.
2. Does not contain muriatic acid.
3. Consumption of 950 ml of P.T.B.-CLEANER for approx. 20 to 30 m² in case of normal fouling. Consumption depends on the condition of the surface.

Mixing ratio	Consumption	Packaging
Light fouling: 1/3 (product/ water); Heavy fouling: 1/1 (product/ water) or pure	950 ml for approx. 20 to 30 m ² in case of normal fouling (depends on the condition of the surface)	950 ml (20 pc/box)
Colours	Soaking time	Application temperature
Colourless	± 5 to 20 minutes	+ 5°C till + 30°C

P.T.B.-CLEANER

Directions for use

- Wet the surface abundantly prior to application.
- Dilute P.T.B.-CLEANER with water.
The rate of dilution depends on the degree of fouling.
Light fouling: dilute 1 part of the product with 3 parts of water.
Heavy fouling: 950 ml of water for 950 ml of P.T.B.-CLEANER or pure.
- Apply P.T.B.-CLEANER with a brush or a low-pressure spraying pistol (prevent the formation of mist). Do not exceed 10 to 15 m² each turn.
- Recommended reaction time: Let it soak in for 5 to 20 minutes depending on the degree of fouling. During the soaking time, keep the floor wet using a diluted solution of P.T.B.-CLEANER.
- Next, rinse thoroughly with water, using a brush, if necessary.

In case of doubt about the acid resistance of the material to be cleaned, test the sensitivity to acid in advance on an inconspicuous spot.

Remarks

- Do not use on materials that are sensitive to acids, such as marble, certain types of natural stone and tiles with high lime content, as well as died synthetics, galvanised and zinc-plated surfaces.
- Do not use on calcareous building materials, such as cement and granite floor coatings, building materials masticated with cement, certain paints, etc.
- Test it in advance on non-ferrous metals.
- Store in a frost-free place.

Safety measures

Wear gloves and safety goggles while working with P.T.B.-CLEANER. Avoid inhalation of vapours. Never mix it with other cleansing agents. Read carefully the safety phrases on the packaging. Ask for the safety data sheet.

