



Tiltrotator

For 30 - 35 ton excavators.

Shallow construction.

Good torsional rigidity.

Cost-effective.

Features :



MCL Central lubrication system

MRT Central Lubrication is a factory-installed central lubrication system that can be connected to the lubrication system of the working machinery. A strong progressive lubrication system genuinely designed for the Nordic winter conditions.



MCS steering controllers

MRT - MACS-proportional steering system with a touchscreen and L8-joysticks. Check our selection of movement systems on page 6-7.

Factory-installed optional extras:



MG Gripper equipment

MRT Gripper, by equipping your working machinery with MRT Gripper, you can further increase the versatility of your equipment.



MPS Rotational sensor

MRT position system. Accurate sensor for 3D machine control systems.

Choose your preferred system: Novatron, Leica, Trimble, or Topcon.

MRT Hydraulic quick couplers

We supply most types of automatic quick coupling systems and tailor them suitable for your needs.

Ask for an offer.

Technical data:	
Width A	638
Width B	405
Width C	385
Width D	912
Width E	707
Weight kg	1360
Pref. hydraulic oil flow l/min.	120
Max. hydraulic pressure -bar	220
Rotational moment kNm:	16
Upper attachment:	Direct, S80
Tool attachment:	S80

