FILTROLL-OIL-30



Compact filterunit 30 l/min pump with two filters in serie

Application

This filtering unit provides double filtering for oil and diesel fuel and absorbs any water and impurities.

The unit features a supply and suction pipe with integrated bottom valve. Sturdy wheeled structure, Large-diameter wheels, Flow rate 30 l/min.

Filtering capacity

- first stage : 5μ nominal prefilter for impurities with paper media Min. order 6 pieces

Efficiency	Ref	Price
5μ nom	F00611030	€/p. 18.17 (x6)

- Second stage : big spin-on fine filter You can choose from the following filters:

Efficiency	Ref	Price		
β25μ>200	ST2862	€/p. 49.74		
<i>β12μ>200</i>	ST2831	€/p. 54.61		
β6μ>200	ST2870	€/p. 58.23		
β3μ>200	ST2840	€/p. 68.81		
β1μ>200	ST28752	€/p. 83.64		
waterabsorptionfilter (0.5 l per filter)				
Efficiency	Ref	Price		
<i>β25μ>75</i>	ST6711	W €/p. 43.98		
Efficiency	Ref	Price		

Vane pump FLOW 30 L/MIN

- Voltage 230/50 Hz. 750 Watt
- Suction, 3m. 3/4 hose with no back valve
- Delivery 3 m 3/4 hose
- Manual nozzle

Optional

Unit can be equipped with electronics for controlling and automating the two functions:

- determine the filtering time in relation to the quantity to be processed,
- switch off automatically in case of filter blockage.

Price

Our Ref: FILTROLL-OIL-30
Net. Price: eur/p. 1212.50
Delivery: 1 p. on stock

Sales Conditions

Prices are excl. 21% BTW
Payment Terms: in advance

Transport : Ex works Belgium, Packing and

Carriage is chargeable at cost

Duration offer: 1 month





FILTROLL-OIL-30



Compact filterunit 30 l/min pump with two filters in serie





