



FILM FACED PLYWOOD ANTI SLIP BIRCH



DESCRIPTION

Film faced plywood anti slip Birch is constructed from multiple layers of Birch with a non slip surface on one side. The panel is class 3 (WBP) glued and is known to be very smooth and easy to saw. Always finish the edges with a suitable sealant when working in damp conditions.

APPLICATIONS

Suitable for intensive applications such as vehicle floors, running boards and other floor coverings.

SIZES

2500 x 1250 mm				3000 x 1500 mm 3050 x 1530 mm			
Thickness (mm)	# / pack	# folds	Standard stock	Thickness (mm)	# / pack	# folds	Standard stock
6.5 mm	65	5		6.5		5	
9 mm	65/80	7	x	9 mm	65	7	x
12 mm	33/	9	x	12 mm	50	9	x
15 mm	40/50	11	x	15 mm	45	11	x
18 mm	22/40	13	x	18 mm	35	13	x
21 mm	30/35	15	x	21 mm	30	15	x
24 mm	26	17	x	24 mm	25	17	
27 mm		19	x	27 mm		19	
30 mm		21	x	30 mm		21	x
35 mm		25					
40 mm		29					

SPECIFICATIONS

FILM

120g/120g
145g/120g
160g/160g

167g/120g
220g/120g
220g/220g

Other options on request

COMPOSITION

Birch wood and possibly a combination of birch and alder wood.

FINISHING

Hexa on request - Fire retardant on request

TOLERANCE

EN-315

SERVICE CLASSES

EN636-3 S

GLUE

EN314-2/3

DENSITY

650 -720 kg/m³

MOISTURE CONTENT

3% - 15%