

PLYWOOD

KIWI PLY



DESCRIPTION

Kiwiply plywood consists of a 100% softwood core bonded with melamine resin and finished with high-quality engineered face veneers.

APPLICATIONS

Suitable for use in humid environments and applicable for both structural and non-structural applications, depending on panel thickness.

SIZES

2500 x 1220 mm 2440 x 1220 mm 2140 x 1220 mm							
Thickness (mm)	# / pack	# folds	Standard stock	Thickness (mm)	# / pack	# folds	Standard stock
3.6 mm	250	3+2		15 mm	60	9+2	x
5 mm	180	3+2	x	18 mm	50	11+2	x
5.5 mm			x	21 mm	43	13+2	x
6 mm	150	5+2	x	22 mm	43	13+2	x
8 mm	113	5+2	x	25 mm		15+2	x
9 mm	100	5+2	x	30 mm			x
10 mm			x	40 mm			x
12 mm	75	7+2	x				

3050 x 1530 mm 3100 x 1525 mm			
Thickness (mm)	# / pack	# folds	Standard stock
5 mm			x
8 mm			x
9 mm	80	5+2	x
10 mm			x
12 mm	45	7+2	x
15 mm	36	9+2	x
18 mm		11+2	x
21 mm		13+2	x
25 mm		15+2	x
30 mm	21		x
40 mm			x

SPECIFICATIONS

SPECIFICATIONS

COMPOSITION

Core: 100% softwood

Finish: high-quality engineered veneer, grade A/A

SERVICE CLASSES

EN636-2S

CE2+ Structural + non structural use

TOLERANCES

0,8 mm according to EN315

GLUE

EN314-2/2 (melamine bonding)

DENSITY

± 560 kg/m³

REACH

Conform (E0.5)

REACTION TO FIRE CLASS

D-s2,d0 (>=9mm)

CERTIFICATE

FSC®