

PLYWOOD PREMIUM



DESCRIPTION

Plywood Premium consists of a phenol bonded core of high quality Eucalyptus hardwood. The edges are sealed and must be treated with a suitable sealant against moisture after installation. Use of full veneers in the long grain direction and composite veneers in the short grain direction, finished with premium engineered veneers.

APPLICATIONS

Suitable for structural applications in humid conditions. For structural and non-structural use (depending on thickness). Direct contact with soil and water should be avoided.

SIZES

2500 x 1220 mm / 2440 1220 mm				3050 x 1530 mm				2140 x 1220 mm			
Thickness (mm)	# / pack	# folds	Stock standard	Thickness (mm)	# / pack	# folds	Stock standard	Thickness (mm)	# / pack	# folds	Stock standard
9 mm				9 mm	80			18 mm	50	11+2	
12 mm	75	7+2	x	12 mm	45	7+2	x	22 mm	41	13+2	
15 mm	60	9+2	x	15 mm	36	9+2	x				
18 mm	50	11+2	x	18 mm		11+2	x				
22 mm	41	13+2	x	22 mm		13+2					
25 mm	36	15+2		25 mm		15+2					
30 mm				30 mm	21						

SPECIFICATIONS

COMPOSITION	Core: 100% Premium Eucalyptus (full long-grain veneers + composite cross-grain veneers) Finish: premium A/A engineered veneer
TOLERANCES	0,3 mm
SERVICE CLASSES	EN636-3 CE2+ Usage structurel et non structurel (selon l'épaisseur)
GLUE	EN314-2/3 (phenolic bonding)
DENSITY	+/- 650 kg/m ³
REACH	Compliant
REACTION TO FIRE CLASS	D-s2,d0 (>=9mm)
CERTIFICATION	FSC® (if indicated and upon request)