



FILM FACED PLYWOOD

BIRCH



DESCRIPTION

Film Faced Birch Plywood consists of several layers of birch wood. The top and bottom faces are a high-quality concrete formwork film. The panel is easy to cut.

APPLICATIONS

Suitable for exterior conditions: horizontal applications such as commercial vehicle and/or trailer floors, animal pens and concrete formwork. Can be used in wet areas.

If the panel is to be used in a wet/damp environment, the edges should always be treated with a suitable edge sealant.

SIZES (mm)

2500 x 1250 mm				3000 x 1500 mm 3050 x 1530 mm				4000 x 2000 mm			
Thickness (mm)	# / pack	# folds	Standard stock	Thickness (mm)	# / pack	# folds	Standard stock	Thickness (mm)	# / pack	# folds	Standard stock
6.5 mm	65	5	x	6.5 mm		5		18 mm	22	13	x
9 mm	65/80	7	x	9 mm	65	7	x				
12 mm	33/	9	x	12 mm	50	9	x				
15 mm	40/50	11	x	15 mm	45	11	x				
18 mm	22/40	13	x*	18 mm	35	13	x				
21 mm	30/35	15	x	21 mm	30	15	x				
24 mm	26	17	x	24 mm	25	17	x				
27 mm		19		27 mm		19					
30 mm		29		30 mm		29					

*Also available in grey and white.

SPECIFICATIONS

FILM	120g/120g 160g/160g 167g/167g 220g/220g 240g/240g
COLOR	Transparent Brown Black White Grey
COMPOSITION	Birch wood and possibly a combination of birch and alder wood.
TOLERANCES	EN-315
SERVICE CLASSES	EN636-3 S
GLUE	EN314-2/3
DENSITY	EN 323: 640 - 740 kg/m ³
MOISTURE CONTENT	3% - 15%