



FILM FACED PLYWOOD

KIWIPLEX 2HP



DESCRIPTION

Kiwiplex film faced plywood consists of a twice hot-pressed, 100% calibrated softwood core bonded with melamine adhesive and finished with a brown concrete film.

SIZES (mm)

2500 x 1250 mm			
Thickness (mm)	# / pack	# folds	Standard stock
4 mm	225	5+2	
9 mm	100	7+2	
12 mm	75	9+2	
15 mm	60	9+2	x
18 mm	50	11+2	x
21 mm	43	13+2	

APPLICATIONS

uitable for use in humid environments and applicable for both structural and non-structural applications, depending on panel thickness.

The panel edges are sealed and must be resealed after cutting.

SPECIFICATIONS

COMPOSITION

Core: 100% softwood, 2G-grade
Finish: brown concrete film, 135 g/m²

PRODUCTION

2x Hot press + calibration

TOLERANCE

0,7 mm according to EN315

SERVICE CLASSES

EN636-2 S
 CE2+ Structural + non structural use (depending the thickness)

REUSES

2-4 (reuses with proper use)

GLUE

EN314-2/2 (melamine bonding)

DENSITY

± 560 kg/m³

REACH

Compliant

REACTION TO FIRE CLASS

D-s2,d0 (>=9mm)

CERTIFICATE

FSC®