

Technical data sheet

PROTECTION MADE EASY

Antislip Bead 500/1000 чm

Description and destination of the product

Antisilip Bead 500/1000 \mu m is an oxyd aluminium bead that is added to floor paints in order to obtain good antislip properties of the floor system.

The bead has an average particle size of 500 to 1000 micron.

Use

Sprinkle the beads onto the freshly applied wet coating, by hand with a "small spreader" or with a special spray gun.

Attention: the beads may not be added to the paint.

To prevent run-out of the beads, this layer must be finished with 1 or 2 additional layers without beads.

Theoretical yield

10-20m²/kg.

Safety measure

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

The last update of our technical data sheets is always available at our website: www.libertpaints.com

Disclaimer

The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.

We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.

Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.