



Technical data sheet

PROTECTION MADE EASY

LIBOTEX

Description and destination of the product

Libotex is an interior wall paint based on a styrene acrylate that is suitable as a primer and finishing layer for projects.

Colour

White and a limited number of colors (e.g. RAL 9010) via dispenser.

Gloss

Matt (≤ 3 GU Gardner 85°).

Technical data

- **Density:** 1.61 (± 0.05) g/cm³
- **Solids content:** 44 % (± 2) in volume
61 % (± 2) in weight
- **Drying times:** Indicative drying times (RH 75%) for 60 micron layer thickness:
Dust-free: 30 min
Dry: 2 hours
Recoatable: 5 hours
- **Lavability** Class 2
- **VOC:** 5 g/l (class A/g)
- **Theoretical yield:** 8-10 m²/l

Surface preparation

The surface must always be clean and dry.

Fungi: first treat with **Fungex** (method: see technical data sheet) followed by thorough cleaning.

Powdering substrates: always first impregnate with **Aquafix**.

New substrates (gyproc, plaster, fiberglass, brick, ...) that do not powder: use **Libotex** as a 2-in-1 system.

The substrate must be sufficiently dry (max. 5% moisture content).

Use

Apply by roller, brush or gun.

Libotex is ready to use.

Libotex as a 2-in-1 system on new substrates: if necessary, dilute the first layer with tap water (5-10%). The tools are best cleaned with tap water immediately after painting.

Application conditions

Libotex can be applied at a temperature above 8°C and a maximum humidity of 85%. These minimum conditions are maintained for the next 48 hours during drying and film formation.

Storage stability

Minimum 18 months in the original, unopened packaging, stored in a frost-free, dry place.

Safety measure

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

The last update of our technical data sheets is always available at our website: www.libertpaints.com

Disclaimer

The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.

We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.

Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.