



Technical data sheet

PROTECTION MADE EASY

Slow Thinner

Description and destination of the product

Slow Thinner is a thinner which is, thanks to its very slow evaporation, very suitable for brush and roller applications.

At high surrounding temperatures or external air displacement (for example wind or outside applications) and where the use of *Thinner 1* isn't sufficient, **Slow Thinner** can be used.

Type of binder

Aromatic hydrocarbons.

Technical data

Density: 0.89 (\pm 0.03) g/cm³

Use

Slow Thinner is recommended to be used with roller/brush applications of one and two pack PUR.

Storage stability

Minimum 2 years in the original, unopened packing in a closed environment at a temperature between -40°C and +50°C.

Safety measure

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

The last update of our technical data sheets is always available at our website: www.libertpaints.com

Disclaimer

The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.

We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.

Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.