



Technical data sheet

PROTECTION MADE EASY

Thinner 16

Description and destination of the product

Thinner 16 is a solvent mixture especially designed for alkyd, vinyl- vinylcopolymer and acrylic systems. **Thinner 16** can also be used to clean the tools used for these paint systems.

Type of binder

Aromatic hydrocarbons.

Technical data

○ **Density:** 0.87 (\pm 0.03) g/cm³

Use

Thinner 16 is recommended as diluant and cleaner for the following paint systems :

- **Primavit** and DA-primers of the fast drying type;
- **Mecavit** and **Mecavit Satin**;
- DM- and DK-varnishes of the fast drying type;
- **Durozinc HS Allprimer**, SA-, SK- and SM-qualities
- Acrylic paints, VK- and VM- qualities.

Storage stability

Minimum 2 years in the original, unopened packing in a covered environment at temperatures between -40°C and +50°C.

Safety measure

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

The last update of our technical data sheets is always available at our website: www.libertpaints.be

Disclaimer

The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect. We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises. Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.