



# Technical data sheet

PROTECTION MADE EASY

---

## Thinner 53

---

### Description and destination of the product

---

**Thinner 53** is thanks to its quick evaporation very suitable for spraying applications of polyurethanes. If there is sufficient flow out and de-aeration, the drying of the paint film can be accelerated by the use of **Thinner 53**.

### Type of binder

---

Solvents based on acetates

### Technical data

---

 **Density:** 0.88 ( $\pm$  0.03) g/cm<sup>3</sup>

### Use

---

**Thinner 53** is recommended for the following paint systems: **Cryltane** and **Mixtane**.

### Packing

---

5 and 25 Litres

### Storage stability

---

Minimum 2 years in the original, unopened packing in a covered environment at temperatures between -40°C and +50°C.

### Safety measure

---

For detailed information about safety measures, personal protection and transport data of this product, we refer to the safety data sheet.

*The last update of our technical data sheets is always available at our website: [www.libertpaints.be](http://www.libertpaints.be)*

#### Disclaimer

*The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Libert Paints doesn't guarantee the functionality or result and takes no responsibility in this respect.*

*We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises.*

*Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.*