



01.02.26 - 31.07.26

20 inserts + toolholder -75%

STEEKBEITELS SUMITOMO GND
PORTE-OUTILS DE TRONCONNAGE SUMITOMO GND




linkse versie is ook beschikbaar - version gauche est aussi possible

options supplémentaires par application

Grooving / Turning			Grooving / Cut-Off			Cut-Off		Profiling	Necking	Non Ferrous Metals
General Type	Low Feed Type		General Type	Low Feed Type	Low Cutting ForceType	Cut-Off Type	Low Cutting ForceType	General Type	General Type	General Type
MG 	ML 		GG 	GL 	GF 	CG 	CF 	RG 	RN 	GA
Cross Section of Cutting Edge	Cross Section of Cutting Edge		Cross Section of Cutting Edge	Cross Section of Cutting Edge	Cross Section of Cutting Edge	Cross Section of Cutting Edge	Cross Section of Cutting Edge	Cross Section of Cutting Edge	Cross Section of Cutting Edge	Cross Section of Cutting Edge
Grooving Width (mm)	Grooving Width (mm)		Grooving Width (mm)	Grooving Width (mm)	Grooving Width (mm)	Grooving Width (mm)	Grooving Width (mm)	Grooving Width (mm)	Grooving Width (mm)	Grooving Width (mm)
1,25 1,5 2,0	1,25 1,5 2,0		1,25 1,5 2,0	1,25 1,5 2,0	1,25 1,5 2,0	1,25 1,5 2,0	1,25 1,5 2,0	1,25 1,5 2,0	1,25 1,5 2,0	1,25 1,5 2,0
3,0 4,0 5,0	3,0 4,0 5,0		3,0 4,0 5,0	3,0 4,0 5,0	3,0 4,0 5,0	3,0 4,0 5,0	3,0 4,0 5,0	3,0 4,0 5,0	3,0 4,0 5,0	3,0 4,0 5,0
6,0 7,0 8,0	6,0 7,0 8,0		6,0 7,0 8,0	6,0 7,0 8,0	6,0 7,0 8,0	6,0 7,0 8,0	6,0 7,0 8,0	6,0 7,0 8,0	6,0 7,0 8,0	6,0 7,0 8,0
Grade	Grade		Grade	Grade	Grade	Grade	Grade	Grade	Grade	Grade
AC8025P AC8035P	AC8025P AC8035P		AC8025P AC8035P	AC8025P AC8035P	AC8025P AC8035P	AC8025P AC8035P	AC8025P AC8035P	AC8025P AC8035P	AC8025P AC8035P	AC8025P AC8035P
AC830P AC425K	AC830P AC425K		AC830P AC425K	AC830P AC425K	AC830P AC425K	AC830P AC425K	AC830P AC425K	AC830P AC425K	AC830P AC425K	AC830P AC425K
AC501S AC502S	AC501S AC502S		AC501S AC502S	AC501S AC502S	AC501S AC502S	AC501S AC502S	AC501S AC502S	AC501S AC502S	AC501S AC502S	AC501S AC502S
AC520U AC530U	AC520U AC530U		AC520U AC530U	AC520U AC530U	AC520U AC530U	AC520U AC530U	AC520U AC530U	AC520U AC530U	AC520U AC530U	AC520U AC530U
AC1030U T2500A	*AC1030U T2500A		AC1030U T2500A	AC1030U T2500A	*AC1030U T2500A	AC1030U T2500A	AC1030U T2500A	T2500A	AC1030U T2500A	T2500A
H10	H10		H10	H10	H10	H10	H10	H10	H10	H10

Ref.	schacht queue	dikte épaisseur	diepte profondeur	plaat plaquette	SET
25.GNDMR.2020.K312	20x20	3	12	25.GCMN3004GG.AC530U	399 €
25.GNDMR.2020.K418	20x20	4	18	25.GCMN4004GG.AC530U	399 €
25.GNDMR.2525.M312	25x25	3	12	25.GCMN3004GG.AC530U	399 €
25.GNDMR.2525.M418	25x25	4	18	25.GCMN4004GG.AC530U	399 €



USE FOR MULTI-PURPOSE OR PROFILING
INSERT FOR TURNING (WIDE GROOVES).

GND5 Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 22 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDM Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm 32 mm x 32 mm → 24 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDM-JE Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 26 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDL Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm 32 mm x 32 mm → 28 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDL-JE Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 30 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDXL New Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 33 Grooving Width (mm) 2,0 3,0 4,0 5,0 6,0 Chipbreaker ML GF RN
---	--	--	--	--	--

GNDF Straight Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 34 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDFS L Type Shank Size Height x Width 25 mm x 25 mm 32 mm x 32 mm → 36 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDMS L Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 24 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDLS L Type Shank Size Height x Width 20 mm x 20 mm 25 mm x 25 mm → 28 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA	GNDIS Straight Type Ø 12 mm Ø 16 mm Ø 20 mm → 40 Grooving Width (mm) 1,5 2,0 3,0 Chipbreaker ML GF	GNDI Straight Type Ø 25 mm Ø 32 mm Ø 40 mm → 38 Grooving Width (mm) 1,25 1,5 2,0 3,0 4,0 5,0 6,0 7,0 8,0 Chipbreaker MG ML GG GL GF CG CF RG RN GA
---	---	---	---	--	--

Internal Machining (≥ 14 mm) Internal Machining (≥ 32 mm)