



MEASUREMENTS	Metric		US
Platform Height	2900	A	9 ft 6 in
Entry Step	400	B	1 ft 3 in
Working Height	4900	C	16 ft
Platform Width	680		2 ft 2 in
Platform Length	1115	D	3 ft 9 in
Platform Length W/decks ext	1710	E	5 ft 6 in
Width	739	F	2 ft 4 in
Base Length	1192	G	3 ft 10 in
Height Stowed	1747	H	5 ft 8 in
Ground Clearance Front	92	J	3,6 in
Ground Clearance Middle	87	K	3,4 in
Platform Capacity w/ decks ext	180 kg		397 lbs
Rated Number of Occupants 			1
Rated Number of Occupants 			2
PERFORMANCE			
Drive Speed Stowed	3 km/h		1.9 mph
Drive Speed Elevated	0,6 km/h		0.35 mph
Inside Turning Radius	Zero		Zero
Outside Turning Radius	1253		4 ft 7 in
Gradeability	35%		35%
Raise/Lower Speed	16 / 21 sec		16 / 21 sec
Controls	One Hand proportional controller		
Tires	Solid Rubber, Non Marking		
POWER			
Power Source	110/220 V ca 24 V 12 Ah automatic		110/220 V ca 24 V 12 Ah automatic
Batteries	2 - 12V 85 Ah		2 - 12V 85 Ah
Hydraulic System Capacity	20 lt		5.3 gal
Unit Weight 	510 kg		1124 lbs
Unit Weight 	550 kg		1212 lbs
STANDARD COMPLIANT	Ansi A92.6, CE Compliant, AS1418.10 (int)		