



DSK-JR | RECTULAR LOUVRE (MULTI-BLADE) DAMPER VALVE



APPLICATION:

For control (modulating) service

RANGE:

Size: DN200x200-4000x4000 or rectangular

CONNECTION:

Flanged, butt-weld

Flange drilling in accordance with: DIN24193 or custom build

INSPECTION & TESTING:

FCI 70-2 Class I & II available (0.5%- KV90)

EN12266

TEMPERATURE RANGE:

-40 / + 750°C

MATERIAL:

Carbon Steel, AISI304, AISI316, AISI253MA, AISI321, AISI309, Alloy 800HT / 625, ...

DESIGN RULES:

EN12516-1, EN12516-2, ANSI 16.34, EN1090

FACE 2 FACE:

Manufacturer standard or according customer specification

OPERATED:

Handlever, gearbox, pneumatic actuator, electrical actuator

DO YOUR NEEDS GO BEYOND A STANDARD PRODUCT?

V.V.C. actively helps you customize your existing products or develops together with you and its engineers, products that are tailored to your application.

Please contact us: info@vvc-valves.com or +32 (0)3 491 97 70

1. air control

2. air on/off

3. exhaust on/off

4. exhaust control

5. ash

6. chimney

7. solids

8. transport