



DSS | HEAVY DUTY BUTTERFLY DAMPER VALVE

APPLICATION:

For On/Off service

RANGE:

DN 50 - 1200

CONNECTION:

Wafer EN1090-1 PN 6, EN1090-1 PN10, ASME B 16.9 Cl. 150 with center holes

INSPECTION & TESTING:

FCI 70-2 Class I, II & III available (0.1% - KV 90)
EN12266

TEMPERATURE RANGE:

-40°C / + 1000°C

MATERIAL:

Carbon Steel, AISI304, AISI316, AISI253MA, AISI321, AISI 309, ...

DESIGN RULES:

EN12516-1, EN12516-2, PED 2014/68/EU, ANSI 16.34

FACE 2 FACE:

Manufacturer standard or according customer specification

OPERATED:

Handlever, gearbox, pneumatic actuator, electrical actuator

DO YOUR NEEDS GO BEYOND A STANDARD PRODUCT?

V.V.C. actively helps you customize your existing products or develops together with you and its engineers, products that are tailored to your application.

Please contact us: info@vvc-valves.com or +32 (0)3 491 97 70

1.
air control

2.
air on/off

3.
exhaust on/off

4.
exhaust control

5.
ash

6.
chimney

7.
solids

8.
transport