



## DSS-D | HEAVY DUTY BUTTERFLY DAMPER VALVE WITH SEALING AIR SYSTEM FOR 100% TIGHTNESS

**APPLICATION:**  
For On/Off service

**RANGE:**  
DN 50 – 1200

**CONNECTION:**  
Wafer EN1090-1 PN 6, EN1090-1 PN10, ASME B 16.9 Cl. 150 with center holes

**INSPECTION & TESTING:**  
FCI 70-2 Class III available (0.1% - KV 90)  
Option: 100% sealing by means of sealing air (fan)  
EN12266

**TEMPERATURE RANGE:**  
-40°C / + 750°C

**MATERIAL:**  
Carbon Steel , AISI304, AISI316, AISI253MA, AISI321, AISI 309, ...

**DESIGN RULES:**  
EN12516-1, EN12516-2, PED 2014/68/EU, ANSI 16.34

**FACE 2 FACE:**  
Manufacturer standard or according customer specification

**OPERATED:**  
Handlever, gearbox, pneumatic actuator, electrical actuator



### DO YOUR NEEDS GO BEYOND A STANDARD PRODUCT?

V.V.C. actively helps you customize your existing products or develops together with you and its engineers, products that are tailored to your application.

**Please contact us:** [info@vvc-valves.com](mailto:info@vvc-valves.com) or +32 (0)3 491 97 70

1. air control

2. air on/off

3. exhaust on/off

4. exhaust control

5. ash

6. chimney

7. solids

8. transport