



## DSK | BUTTERFLY DAMPER VALVE

**APPLICATION:**  
For On/off service

**RANGE:**  
DN 250 – 4000

**CONNECTION:**  
Flanged, butt-weld  
Flange drilling in accordance with:  
EN1092-1, DIN86044, DIN28031, JIS(7805-5K-10K), ASME B 16.5 Cl. 150 or 300,  
ASME 16.47 Serie A, B or Custom build

**INSPECTION & TESTING:**  
FCI 70-2 Class I, II & III available (0.1%- KV90)  
Option: 100% tight (ISV) - with inflatable seal – Ts: 160°C and +0.9/-0.9 barG  
EN12266

**TEMPERATURE RANGE:**  
-40 / + 750°C

**MATERIAL:**  
Carbon Steel, AISI304, AISI316, AISI253MA, AISI321, AISI309, Alloy 800HT / 625, ...

**DESIGN RULES:**  
EN12516-1, EN12516-2, ANSI 16.34, EN1090

**FACE 2 FACE:**  
Manufacturer standard or according customer specification

**OPERATED:**  
Handlever, gearbox, pneumatic actuator, electrical actuator

### DO YOUR NEEDS GO BEYOND A STANDARD PRODUCT?

V.V.C. actively helps you customize your existing products or develops together with you and its engineers, products that are tailored to your application.

**Please contact us:** info@vvc-valves.com or +32 (0)3 491 97 70



- 1.  
air control
- 2.  
air on/off
- 3.  
exhaust on/off
- 4.  
exhaust control
- 5.  
ash
- 6.  
chimney
- 7.  
solids
- 8.  
transport